
Beam Halo and Abort Gap Monitoring

R.J. Tesarek Fermilab (1/13/04)

Calculating Losses

Beam Losses all calculated in the same fashion

- Detector signal in coincidence with beam passing the detector plane.
- ACNET variables differ by detector/gating method.




Detectors

Halo Counters

066 48.6 cm 014 45.7 cm 59.1 cm 040 West Alcove floor

Beam Shower Counters



ACNET variables:

B0PHSM: beam halo

BOPBSM: abort gap losses


B0PAGC: 2/4 coincidence abort gap losses

B0PLOS: proton losses (digital)

LOSTP: proton losses (analog)

BOMSC3: abort gap losses (E*W coincidence)


Beam Monitors



BSC counters: monitor beam losses and abort gap


Halo counters: monitor beam halo and abort gap

Documentation




http://www-cdfonline.fnal.gov/acnet/ACNET_beamquality.html

Beam Halo Counters




Re-calibrating abort gap rates



1/7/04: B0MSC3 back online (M.Binkley)

Use naive scaling to connect new/old B0PAGC rates.

$$Rate_{(Jan04)} = Scale \cdot Rate_{(Aug03)}$$
$$Scale = \frac{slope_{(Jan04)}}{slope_{(Aug03)}} = \frac{43.8}{12.8} = 3.3$$



B0MSC3 (Hz)

References

Beam and Halo Monitoring:

```
M. Karagoz-Unel, R.J. Tesarek, NIM <u>A506</u> (2003) 7-19.
```

M. Gallinaro, FERMILAB-CONF-02-121-E(2002) 11.

http://www-cdfonline.fnal.gov/acnet/ACNET_beamquality.html

Beam Induced Backgrounds and Radiation:

http://ncdf67.fnal.gov/~tesarek/halo/joint_physics/020503

CDF note: 5873 CDF note: 5926

CDF note: **5960**

CDF note: **6753**

CDF note: 6761